

### 1. Identification

**Manufacturer:**  
INEOS Styrolution America LLC  
4245 Meridian Parkway, Suite 151  
Aurora IL 60504  
USA  
www.ineos-styrolution.com  
E-mail: infopoint.americas@styrolution.com

**EMERGENCY  
CHEMTREC**  
Telephone: 1 - 800 - 424 - 9300 (24 h)  
(collect calls accepted)  
Information Phone: +1 866 - 890 - 6353

**INEOS Styrolution Product Name:** Lustran® 348 WT012002  
**INEOS Styrolution Material Number:** 50020904, 50020905, 50020906  
**INEOS ABS Product Name**  
(Formerly known as): LUSTRAN ABS 348 012002  
**INEOS ABS Material Number** 3579798, 2997022, 3635817, 887738, 3883020

**Chemical Family:** Thermoplastic Polymer  
**Chemical Name:** Acrylonitrile/Butadiene/Styrene Terpolymer  
**Synonyms:** ABS  
**Recommended Use:** Manufacture of polymeric articles  
**Restrictions on Use:** None known

**SDS Date of Preparation/Revision:** 05/31/2017

### 2. Hazards Identification

#### GHS Classification:

Health	Environmental	Physical
None	None	Combustible Dust

#### Label Elements

##### WARNING!

May form combustible dust concentrations in air

##### Supplemental Labeling:

May form combustible dust concentrations in air during processing. Melted product is flammable and produces intense heat and dense smoke during burning. Irritating gases and fumes may be given off during burning or thermal decomposition. May cause mechanical irritation (abrasion). Causes slipping hazard if spilled. Contact with hot material will cause thermal burns.

### 3. Composition/Information on Ingredients

#### Components

<u>Weight %</u>	<u>Components</u>	<u>CAS-No.</u>
>=1%	Acrylonitrile/Butadiene/Styrene Terpolymer	9003-56-9
>=1%	N,N-Ethylenebisstearamide	110-30-5
1-5%	Titanium Dioxide	13463-67-7
<0.1%	Styrene	100-42-5

The exact concentrations are a trade secret.

#### 4. First Aid Measures

**Eye Contact:** In case of eye contact, flush eyes with plenty of lukewarm water.

**Skin Contact:** In case of contact with skin, wash affected areas with soap and water. In case of thermal burns, immediately immerse affected area in cold water. Do not attempt to remove material adhering to the skin. Get medical attention for burns.

**Inhalation:** If exposed to gases or fumes from thermal processing, move to fresh air. Get medical attention, if irritation or other symptoms develop and persist.

**Ingestion:** Not a likely route of exposure. If swallowed, get medical attention.

**Most Important Symptoms:** Contact with heated material can cause thermal burns. Gases and fumes evolved during thermal processing or decomposition of this material may irritate the eyes, skin or respiratory tract and cause nausea, drowsiness and headache.

**Indication of Immediate Medical Attention and Special Treatment, if Needed:** Medical attention may be needed for treatment of burns.

#### 5. Fire-Fighting Measures

**Suitable (Unsuitable) Extinguishing Media:** Water, foam, dry chemical, carbon dioxide (CO<sub>2</sub>).

**Specific Hazards Arising from the Chemical:** Toxic and irritating gases and fumes may be given off during burning or thermal decomposition. Avoid generating dust. Fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard. Hazardous combustion products include carbon dioxide, carbon monoxide, styrene, acrylonitrile, hydrogen cyanide, hydrocarbons.

**Special Protective Equipment and Precautions for Fire-Fighters:** Firefighters should be equipped with self-contained breathing apparatus to protect against potentially toxic and irritating fumes.

#### 6. Accidental Release Measures

**Personal Precautions, Protective Equipment And Emergency Procedures:** Wear appropriate protective clothing as described in Section 8.

**Methods And Materials For Containment/Cleanup:** If molten, allow material to cool and place into an appropriate marked container for disposal. Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Avoid dispersal of dust in the air (i.e., removing dust from surfaces with compressed air). Non-sparking tools should be used.

#### 7. Handling and Storage

**Precautions for Safe Handling:** Handle in accordance with good industrial hygiene and safety practices. Wash thoroughly after handling. Avoid breathing dust. Use with adequate ventilation.

Minimize dust generation and accumulation. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces.

Pellets and pellet dust can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres.

Protect equipment (e.g. storage bins, conveyors, dust collectors) with explosion vents.

**Conditions for Safe Storage, including any incompatibilities:** Store in a dry, well-ventilated area.

**Storage Temperature:** 82°C (179.6°F) maximum

**Storage Period:** Not established

## 8. Exposure Controls / Personal Protection

### Exposure Guidelines:

#### United States

Although no exposure limit has been established for this product, the OSHA PEL for Particulates not Otherwise Regulated (PNOR) of 15 mg/m<sup>3</sup> total dust, 5 mg/m<sup>3</sup> respirable fraction is recommended.

Chemical	OSHA PEL	ACGIH TLV
Titanium Dioxide	15 mg/m <sup>3</sup> total dust TWA	10 mg/m <sup>3</sup> TWA
Styrene	100 ppm TWA 200 ppm Ceiling 600 ppm Maximum concentration (5 min in any 3 hrs)	20 ppm TWA 40 ppm STEL
N,N-Ethylenebisstearamide	None Established	None Established

#### Canada

Although no exposure limit has been established for this product, applicable provincial exposure limits for particles not otherwise classified/ specified are recommended.

Provinces	Chemical	Exposure Limits
Alberta; Manitoba; New Brunswick; New Foundland/Labrador; Northwest Territories; Nova Scotia; Prince Edward Island	Styrene	20 ppm TWA 40 ppm STEL
British Columbia	Styrene	50 ppm TWA 75 ppm STEL
Nunavut; Québec; Saskatchewan	Styrene	50 ppm TWA 100 ppm STEL
Ontario	Styrene	35 ppm TWA 100 ppm STEL
Yukon	Styrene	100 ppm TWA 125 ppm STEL
Alberta; British Columbia, Manitoba; New Brunswick; New Foundland/Labrador; Nova Scotia; Ontario, Prince Edward Island, Québec	Titanium Dioxide	10 mg/m <sup>3</sup> TWA
Northwest Territories, Nunavut	Titanium Dioxide	5 mg/m <sup>3</sup> TWA (respirable), 10 mg/m <sup>3</sup> TWA (total dust)
Saskatchewan, Yukon	Titanium Dioxide	10 mg/m <sup>3</sup> TWA 20 mg/m <sup>3</sup> STEL
All Provinces	N,N-Ethylenebisstearamide	None Established

**Appropriate Engineering Controls:** General dilution and local exhaust as necessary to control airborne vapors, mists, dusts and thermal decomposition products below appropriate occupational exposure limits. It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling this product contain explosion relief vents or an explosion suppression system or an oxygen deficient environment. Ensure that dust handling systems (such as exhaust ducts, dust collectors, vessels and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e. there is no leakage from the equipment).

### Personal Protective Equipment:

**Respiratory Protection:** If the recommended exposure limits are exceeded a NIOSH approved particulate/organic vapor respirator appropriate for the form and concentration of the contaminants should be used. Selection and use of respiratory equipment must be in accordance with OSHA 1910.134 or other applicable regulations and good industrial hygiene practice.

**Hand Protection:** Wear heat resistant gloves when handling molten material.

**Eye Protection:** Safety glasses with side shields.

**Skin and Body Protection:** No special protection required for normal handling and use. For operations where heated polymer is handled, thermally protective gloves and clothing should be worn along with appropriate eye protection.

**Additional Protective Measures:** Employees should wash their hands and face before eating, drinking, or using tobacco products. Educate and train employees in the safe use and handling of this product. Purgings should be collected as small flat, thin shapes or thin strands to allow for rapid cooling. Precautions should be taken against autoignition of hot, thick masses of the plastic. Quench with water. Fumes or vapors emitted from the hot melted plastic during converting operations may condense on cool overhead metal surfaces or exhaust ducts. The condensate, usually in the form of a soft, grease-like semi-solid may contain substances which can be irritating or toxic. Wear rubber gloves when cleaning contaminated surfaces.

Use only appropriately classified electrical equipment and powered industrial trucks where dust from product is present.

### 9 Physical and Chemical Properties

<b>Form:</b>	Solid	<b>Appearance:</b>	Pellets
<b>Color:</b>	White	<b>Odor:</b>	Slight, sweet, aromatic
<b>pH:</b>	Not applicable	<b>Odor Threshold:</b>	0.15 to 25 ppm (styrene)
<b>Boiling Point/Range:</b>	Not applicable	<b>Vapor Density:</b>	3.6 (styrene)
<b>Melting point/freezing point:</b>	Not established	<b>Evaporation Rate:</b>	Not applicable
<b>Flammability (solid, gas):</b>	Dust and molten material are combustible	<b>Partition coefficient (n-octanol/water):</b>	Not applicable
<b>Viscosity:</b>	Not applicable	<b>Softening Point:</b>	82-107°C (179-224°F)
<b>Flash Point:</b>	388-400°C (730-752°F)	<b>Vapor Pressure:</b>	Not applicable
<b>Lower Explosion Limit:</b>	Not established	<b>Bulk Density:</b>	600-700 kg/m <sup>3</sup>
<b>Upper Explosion Limit:</b>	Not established	<b>Relative Density:</b>	Approx. 1.05
<b>Autoignition Temperature:</b>	495-510°C (923-950°F)	<b>Solubilities:</b>	Insoluble in water
<b>Decomposition Temperature:</b>	Approx. 260°C (500°F)		

### 10. Stability and Reactivity

**Reactivity:** Hazardous polymerization does not occur.

**Chemical Stability:** Stable

**Possibility of Hazardous Reactions:** None known.

**Conditions to Avoid:** None known

**Incompatible Materials:** None known

**Hazardous Decomposition:** Thermal decomposition will generate carbon dioxide, carbon monoxide, styrene, acrylonitrile, hydrogen cyanide, hydrocarbons.

### 11. Toxicological Information

#### HUMAN HEALTH EFFECTS AND SYMPTOMS OF EXPOSURE

**Skin (Acute):** Contact with heated material can cause thermal burns.

**Eye (Acute):** May cause mechanical irritation.

### **General Effects of Exposure**

**Acute Effects of Exposure:** Gases and fumes evolved during thermal processing or decomposition of this material may irritate the eyes, skin or respiratory tract and cause nausea, drowsiness and headache.

**Chronic (non-cancer) Effects of Exposure:** Not expected to cause any adverse chronic health effects.

### **Carcinogenicity:**

The Agency for Toxic Substances & Disease Registry concluded in their 2007 Toxicological Profile for Styrene that styrene may possibly be a weak human carcinogen. The EPA has not given a formal carcinogen classification to styrene stating "Several epidemiologic studies suggest there may be an association between styrene exposure and an increased risk of leukemia and lymphoma. However, the evidence is inconclusive due to confounding factors." In 2011 the National Toxicology Program listed styrene as reasonably anticipated to be a human carcinogen based on limited evidence from studies in humans, sufficient evidence from studies in experimental animals, and supporting data on mechanisms of carcinogenesis.

Styrene                            **IARC** – Overall evaluation: 2B Possible carcinogen  
   **IARC** – Evidence of carcinogenicity in animals: Limited data  
   **IARC** – Evidence of carcinogenicity in humans: Limited data  
   **NTP** - Reasonably anticipated to be a human carcinogen  
   **ACGIH** – A4: Not classifiable as a Human Carcinogen

Titanium Dioxide (Rutile) **IARC** – Overall evaluation: 2B Possible carcinogen  
   **IARC** – Evidence of carcinogenicity in animals: Sufficient data  
   **IARC** – Evidence of carcinogenicity in humans: Inadequate data  
   **ACGIH** – A4: Not classifiable as a Human Carcinogen

### **Product Toxicity Data**

**Toxicity Note:** Toxicity data is based on similar ABS resins.

**Skin Irritation:** rabbit – non-irritating.

**Eye Irritation:** rabbit – Draize – slightly irritating.

**Other Relevant Toxicity Information:** Styrene is slightly toxic to practically non-toxic in oral feeding studies (rats) and skin application studies (rabbits). Repeated inhalation studies in rats for 3 weeks reported effects suggestive of a hearing impairment. Repeated inhalation exposures produced lung irritation in guinea pigs and organ weight changes in rats. Styrene caused lung tumors in several strains of mice by inhalation and oral exposure. The evidence in rats is insufficient for reaching a conclusion concerning the carcinogenicity of styrene. There is limited evidence for the carcinogenicity of styrene in humans based on studies of workers that showed an increased mortality from or incidence of cancer of the lymphohematopoietic system and increased levels of DNA adducts and genetic damage in lymphocytes from exposed workers. However, the types of lymphohematopoietic cancer observed in excess varied across different studies and excess risk was not found in all cohorts. In standard mutagenicity tests, both positive and negative results were reported. No birth defects occurred in rats given styrene orally. Some toxic effects on the fetus were noted in a limited inhalation study using repeated high doses.

### **Toxicity Data for Acrylonitrile/Butadiene/Styrene Terpolymer**

**Acute Oral Toxicity:** LD50 >5000 mg/kg (rat)

**Acute Dermal Toxicity:** LD50 >2,000 mg/kg (rabbit) estimated

**Skin Irritation:** rabbit – Draize – No skin irritation

**Eye Irritation:** rabbit – Slightly irritating

**Sensitization:** Dermal – non-sensitizer (guinea pig Buehler Test)

**Toxicity Data for N,N-Ethylenebisstearamide**

**Acute Oral Toxicity:** LD50 >15,380 mg/kg (rat)

**Acute Inhalation Toxicity:** LC50 >58.2 mg/L/1 hr (rat)

**Acute Dermal Toxicity:** LD50 >20,000 mg/kg (rabbit)

**Skin Irritation:** rabbit – Slightly-irritating

**Eye Irritation:** rabbit – Slightly irritating

**Repeated Dose Toxicity**

15 weeks, oral, NOAEL <0.5% (rat, male/female, daily)

**Mutagenicity**

Genetic Toxicity in Vitro:

Ames: negative (Salmonella typhimurium, metabolic activation with and without)

**Carcinogenicity**

Rat, Male/Female, oral, 2 years, daily: Did not show carcinogenic effect

**Toxicity Data for Titanium Dioxide**

**Acute Oral Toxicity:** LD50 >5,000 mg/kg (rat)

**Acute Inhalation Toxicity:** LC0 >6.82 mg/L/4 hr (rat)

**Acute Dermal Toxicity:** LD50 >5,000 mg/kg (rabbit)

**Skin Irritation:** rabbit – non-irritating

**Eye Irritation:** rabbit – Draize – non-irritating

**Sensitization:** Dermal – non-sensitizer (guinea pig maximization test (GPMT)), non-sensitizer human patch test

**Repeated Dose Toxicity**

28 Days, inhalation NOAEL 35 mg/m<sup>3</sup> (rat)

**Mutagenicity**

Genetic Toxicity in Vitro:

Ames: negative (Salmonella typhimurium, metabolic activation with and without)

Genetic Toxicity in Vivo:

Drosophila SLRL test: negative (Drosophila melanogaster)

**Carcinogenicity**

In lifetime inhalation studies of rats, airborne respirable-sized titanium dioxide particles were shown to cause lung tumors at concentrations associated with substantial lung burdens and pulmonary overload. Mice and hamsters did not develop lung tumors under similar testing conditions.

**Toxicity Data for Styrene**

**Acute Oral Toxicity:** LD50 1000 mg/kg (rat)

**Acute Inhalation Toxicity:** LC50 11.8 mg/L/4 hr (rat)

**Acute Dermal Toxicity:** LD50 >20,000 mg/kg (rabbit)

**Skin Irritation:** rabbit – Draize – moderately irritating

**Eye Irritation:** rabbit – Draize – severely irritating

**Sensitization:** Dermal – non-sensitizer (guinea pig maximization test (GPMT))

#### **Repeated Dose Toxicity**

6 months, inhalation NOAEL 6.3 mg/kg (monkey, male/female, daily)

28 Days, dermal NOAEL <500 mg/kg (rat, male daily)

13 weeks, inhalation NOAEL 0.565 mg/L (rat, male/female, daily)

#### **Mutagenicity**

Genetic Toxicity in Vitro:

Ames: negative (Salmonella typhimurium, metabolic activation with and without)

Sister Chromatid Exchange: positive (human lymphocytes, metabolic activation with and without)

Genetic Toxicity in Vivo:

Cytogenic assay positive (rat)

Drosophila SLRL test: positive (Drosophila melanogaster)

#### **Carcinogenicity**

Styrene was tested for carcinogenicity in rats in four gavage studies, one drinking water study and two inhalation studies. Overall, there was no reliable evidence for an increase in tumor incidence in rats in any of these studies. Inhalation exposure caused benign lung tumors (alveolar/bronchiolar adenoma) and increased the combined incidence of benign and malignant lung tumors (alveolar/bronchiolar adenoma and carcinoma) in CD-1 mice of both sexes; in females, it also increased the separate incidence of malignant lung tumors. In male B6C3F1 mice, oral exposure to styrene increased the combined incidence of benign and malignant lung tumors (alveolar/bronchiolar adenoma and carcinoma), and a positive dose-response trend was observed (NCI 1979). These findings are supported by findings of lung tumors in both sexes of O20 mice exposed to styrene (Ponomarev and Tomatis 1978). In O20 mice, a single dose of styrene was administered to pregnant dams on gestational day 17, and pups were exposed orally once a week for 16 weeks after weaning. A significantly increased incidence and earlier onset of benign and malignant lung tumors combined (adenoma and carcinoma) occurred in mice of both sexes as early as 16 weeks after weaning. In a similar study with C57Bl mice administered a much lower dose of styrene, lung-tumor incidence was not significantly increased. A screening study by intraperitoneal administration did not find an increase in tumor incidence or multiplicity in mice. The increased risks for lymphatic and hematopoietic neoplasms observed in some human epidemiological studies are generally small, statistically unstable and are not very robust.

#### **Toxicity to Reproduction/Fertility**

Three generation study, oral, daily (rat, male/female) NOAEL (parental): 250 ppm, NOAEL (F1): 125 ppm, NOAEL (F2): 125 ppm

No effects on reproductive parameters observed at doses tested.

Other method, inhalation, daily, (rabbit female) NOAEL parental 2.6 mg/L, NOAEL (F1) 2.6 mg/L

#### **Developmental Toxicity/Teratogenicity**

Rat, female inhalation, gestation NOAEL (teratogenicity): >600 ppm, NOAEL (maternal) : <300 ppm. No teratogenic effects observed at doses tested.

Rabbit, female, inhalation, daily, gestation, NOAEL (teratogenicity): >600 ppm, NOAEL (maternal) : >600 ppm.

Fetotoxicity seen only with maternal toxicity.

## **12. Ecological Information**

### **Ecological Data for Acrylonitrile/Butadiene/Styrene Terpolymer**

**Biodegradation:** Not readily biodegradable

**Bioaccumulation:** Does not bioaccumulate

**Acute and Chronic Toxicity to Fish**

LC50: 18 mg/L/96 hr common carp (*cyprinus carpio*)

**Ecological Data for N,N-Ethylenebisstearamide**

**Biodegradation:** aerobic 15% 28 d

**Toxicity to Microorganisms**

EC50 >1000 mg/L/3 hr activated sludge microorganisms

**Ecological Data for Titanium Dioxide**

**Acute and Chronic Toxicity to Fish**

LC0 >1000 mg/L/48 hr Golden Orfe (*leuciscus idus*)

**Acute Toxicity to Aquatic Invertebrates**

EC50 > 3 mg/L water flea (*daphnia magna*)

**Toxicity to Microorganisms**

EC0 >10,000 mg/L/24 hrs *pseudomonas fluorescens*

EC0 >5000 mg/L *Escherichia coli*

**Ecological Data for Styrene**

**Biodegradation:** aerobic 71% 28 d

**Biological Oxygen Demand (BOD):** 5 days, 2.46 mg/L

**Chemical Oxygen Demand:** 2800-2880 mg/g

**Theoretical Biological Oxygen Demand (ThBOD):** 3.07 mg/L

**Bioaccumulation:** Carp 13.5 BCF

**Acute and Chronic Toxicity to Fish**

LC50 9 mg/L/96 hr sheepshead minnow (*cyprinodon variegatus*)

LC50 29 – 59.3 mg/L/96 hr fathead minnow (*pimephales promelas*)

LC50 25 mg/L/96 hr bluegill (*lepomis macrochirus*)

LC50 2.4 – 4.1 mg/L/96 hr rainbow trout (*salmo gairdneri*)

**Acute Toxicity to Aquatic Invertebrates**

EC50 4.7 – 23 mg/L/48 hr water flea (*daphnia magna*)

**Toxicity to Aquatic Plants**

EC50 1.4 mg/L/72 hr green algae (*selenastrum capricornutum*)

**Toxicity to Microorganisms**

EC50 approx. 500 mg/L/30 min activated sludge microorganisms

EC50 5.5 mg/L/5 min *photobacterium phosphoreum*

EC50 72 mg/L/16 hr *pseudomonas putida*

### 13 Disposal Considerations

#### Waste Disposal Method

Waste disposal should be in accordance with existing federal, state, provincial, and/or local environmental control laws.

### 14. Transportation Information

**Land Transport (DOT):** Not Regulated

**Land Transport (TDG):** Not Regulated

**Sea Transport (IMDG):** Not Regulated

**Air Transport (ICAO/IATA):** Not Regulated

### 15. Regulatory Information

#### United States Federal Regulations

**US OSHA Hazard Communication Classification:** This product is hazardous under the criteria of the Federal OSHA Hazard Communication Standard (29 CFR 1910.1200).

**US Toxic Substance Control Act:** All the components of this product are listed on the TSCA Inventory

**US EPA CERCLA Hazardous Substances (40 CFR 302):**

**Components**

Styrene 100-42-5 <0.1% RQ=1000 lbs

**SARA Section 311/312 Hazard Categories:** See Section 2 for OSHA Hazard Classification

**US EPA Emergency Planning and Community Right to Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A):**

**Components**

None

**Section 313 Toxic Chemicals (40 CFR 372.65) – Supplier Notification Required:**

**Components**

Styrene 100-42-5 <0.1%

**US EPA Resource Conservation and Recovery Act (RCRA) Composite List of Hazardous Wastes and Appendix VIII Hazardous Constituents (40 CFR 261):**

If discarded in purchased form, this product would not be a hazardous waste either by listing or by characteristic. However, under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste (40 CFR 261.20-24).

#### **State Right-to-Know Information**

The following chemicals are specifically listed by individual states; other product specific data in other sections of the SDS may also be applicable for state requirements. For details on your regulatory requirements you should contact the appropriate agency in your state.

#### **Massachusetts, New Jersey or Pennsylvania Right to Know Substance Lists**

**Weight%**

**Components**

**CAS-No.**

>=1%

Acrylonitrile/Butadiene/Styrene Terpolymer

9003-56-9

>=1%

N,N-Ethylenebisstearamide

110-30-5

1-5%

Titanium Dioxide

13463-67-7

**New Jersey Environmental Hazardous Substance List and/or New Jersey RTK Special Hazardous Substances Lists:**

<u>Weight%</u>	<u>Components</u>	<u>CAS-No.</u>
<0.1%	Styrene	100-42-5

**Pennsylvania Right to Know Special Hazardous Substance List:**

<u>Weight%</u>	<u>Components</u>	<u>CAS-No.</u>
<=0.01%	Acrylonitrile	107-13-1

**MA Right to Know Extraordinarily Hazardous Substance List:**

<u>Weight%</u>	<u>Components</u>	<u>CAS-No.</u>
<0.1%	Styrene	100-42-5
<=0.01%	Acrylonitrile	107-13-1

**California Proposition 65:**

**Warning! This product contains a chemical(s) known to the State of California to cause cancer.**

<u>Weight%</u>	<u>Components</u>	<u>CAS-No.</u>
<=0.01%	Acrylonitrile	107-13-1
<0.1%	Styrene	100-42-5

**Canadian Regulations**

**Canadian CEPA Status:** All of the components of this product are listed on the DSL.

**International Inventories**

**AUSTRALIAN INVENTORY (AICS):** Not Determined

**CANADA INVENTORY (DSL):** Listed

**CHINA INVENTORY (IECSC):** Listed

**EU INVENTORY (EINECS/ELINCS):** Listed

**JAPAN INVENTORY (ENCS):** Not Determined

**KOREA INVENTORY (ECL):** Listed.

**PHILIPPINE INVENTORY (PICCS):** Listed

**UNITED STATES (TSCA):** Listed.

**NEW ZEALAND INVENTORY:** Not Determined

**16. Other Information**

Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosion from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling.

**NFPA 704M Rating**

<b>Health</b>	0
<b>Flammability</b>	1
<b>Instability</b>	0
<b>Other</b>	

0=Insignificant 1=Slight 2=Moderate 3=Serious 4=Extreme

**HMIS Rating**

<b>Health</b>	0
<b>Flammability</b>	1
<b>Physical Hazard</b>	0

0=Minimal 1=Slight 2=Moderate 3=Serious 4=Severe

\* Chronic Health Hazard

INEOS Styrolution America LLC's method of hazard communication is comprised of Product Labels and Safety Data Sheets. HMIS and NFPA ratings are provided by INEOS Styrolution America LLC as a customer service.

Contact Person: Product Safety Department  
Telephone: +1 866 - 890 - 6353  
SDS Number: STN002029  
Version Date: 05/31/2017  
Report Version 2.0

The information is furnished without warranty, expressed or implied. This information is believed to be accurate to the best knowledge of INEOS Styrolution America LLC. The information in this SDS relates only to the specific material designated herein. INEOS Styrolution America LLC assumes no legal responsibility for the use or reliance upon the information in this SDS.